



12N9-BS

Valve-regulated lead-acid battery



NESSCAP

Characteristics

Model		12N9-BS
Capacity(Ah)		9
Dimensions (MM) L*W*H	Length	137
	Width	76
	Height	134
UNIT WEIGHT (KG)		2.70
PCS/CNT		8

Overview

Nesscap Pvt. Ltd. General Purpose series batteries are designed with state-of-the-art AGM (absorbent glass mat) technology, high-performance plates and electrolyte. With excellent value and characteristics, this range is suitable for all general purpose application.



QUALITY

Primary competitive advantages

- 100% Pre-delivery inspection to ensure stable quality and reliable performance
- Pb-Ca grid alloy battery plate, low water loss, and stable quality low self-discharge rate.
- Complete sealed, maintenance free, low self-discharge rate, good sealing property.
- Low Internal resistance, good high rate discharge performance.
- Excellence high-and-low temperature performance, working temperature ranging from -30°C to 50°C.
- Design float service life: 3-5 years.

Construction

Component	+ve Plate	-ve Plate	Seperator	Electrolyte	Safety Valve	Terminal
Raw Material	Lead dioxide	Lead	AGM	Sulfuric Acid	Rubber	Copper

The above characteristics represent average values and can be obtained within three charge and discharge cycles. The batteries must be fully charged before testing. The data in this document is subject to change without notice and become contractual only after written confirmation. Please contact NESSCAP Pvt. Ltd. for the latest available version.